



BARRA FISSA CM.80 DX/SX SERIE NYLON Ø35

fixed bar cm.80 rh/lh series Nylon Ø35

	cm	Kg
AN-B03/XX	80	3,74



bianco lucido RAL 9016	blu lucido RAL 5002	verde lucido RAL 6005	giallo lucido RAL 1003	rosso lucido RAL 3002	grigio lucido RAL 7004	nero lucido RAL 9005
------------------------------	---------------------------	-----------------------------	------------------------------	-----------------------------	------------------------------	----------------------------



testo di capitolato:

barra fissa orizzontale di sicurezza Ø35 mm, universale dx/sx con rinforzo laterale di portata, realizzata in tubo di alluminio 2 mm., rivestita con materiale termoplastico nylon (poliammide 6), spessore 2 mm, caldo al tatto, unita con giunti di innesto in nylon e barra filettata in acciaio, completa di: vite svasata di unione Ø8, piattelli per fissaggio in nylon, a 6 fori, rosoni acciaio inox funzione "antivandalo". dimensione mm 800(p) x 212(l) x 225(h).

tipo Goman codice AN-B03/XX

specifications:

fixed horizontal safety bar Ø35 mm, universal right/left with side reinforcement of capacity, made of 2 mm aluminum tube, coated with thermoplastic nylon (polyamide 6), thickness 2 mm, warm to the touch, nylon couplings and steel threaded bar, complete with: Ø8 countersunk union screw, nylon fixing plates, 6 holes, stainless steel roses "vandal-proof" function. dimension mm 800 (p) x 212 (l) x 225 (h). type Goman code AN-B03/XX

