



RUBINETTO LAVABO ELETTRONICO CROMATO A CORRENTE 220V

chrome electronic washbasin tap - power supply 220V

	cm	Kg
D07024C/99	5,5x14,6	2,7



cromo

99

Il funzionamento del rubinetto è garantito solo con acqua priva di impurità, è quindi fondamentale installare un filtro. Disponibile premiscelatore sottolavabo D09020/99.

testo di capitolato:

rubinetto cromato elettronico a infrarossi per lavabo con dispositivo antivandalo di blocco dell'acqua, alimentazione con trasformatore a 220V. pressione minima 0,5 bar. pressione massima 4 bar. temperatura massima 70°C. distanza minima sensore 0,5 cm. distanza massima sensore 10 cm. portata 5 lt/min a 3 bar. dotato di valvola di non ritorno, sensore antidiurbo, sistema antivandalo di blocco dell'acqua. dimensioni mm 146x151x55.

tipo Goman codice D07024C/99

The operation of the tap is guaranteed only with water free of impurities, it is therefore essential to install a filter. D09020/99 under basin pre-mixer available.

specifications:

infrared electronic chrome faucet for washbasin with anti-vandal water blocking device, 220V transformer power supply. minimum pressure 0.5 bar. maximum pressure 4 bar. maximum temperature 70°C. minimum sensor distance 0.5 cm. maximum sensor distance 10 cm. flow rate 5 l/min at 3 bar. equipped with non-return valve, anti-interference sensor, anti-vandal water blocking system. dimensions 146x151x55 mm. Goman type code D07024C/99

